

LoRaWAN® Gateway, SenseCAP M2

code: SP042



LoRaWAN® Gateway - a complete solution for implementing LoRa and COMET Cloud.

The proven WAP design ensures reliable performance even in harsh weather conditions. The device supports the 863-870 MHz frequency range.

The LoRaWAN® Gateway is pre-configured for operation in COMET Cloud, ensuring quick and seamless integration into the system.

LoRaWAN® Gateway comes with an external antenna with a magnetic base and a 230 V AC/12 V DC power adapter.

Comparison of Available LoRa Gateway Models:

[SP041 MikroTik wAP](#) - suitable for indoor installations thanks to the built-in antenna, with the option of outdoor use due to its IP54 rating.

[SP042 SenseCAP M2](#) - higher sensitivity to radio signals thanks to the external antenna. Intended for indoor use only (not resistant to weather conditions, lacks higher IP rating), suitable for environments where an external antenna is not an issue.

Technical data

CHARACTERISTICS	
LoRa Frequency	EU868, RU864, IN865
Ethernet	10/100 Mbps, podpora PoE PD
LoRa antenna	External 3dBi antenna 50ohm with magnetic base, height 29 cm, supply cable length 1 m
POWER	
DC jack input Voltage	12 V / 2A
PoE in input Voltage	(IEEE 802.3 af), 40-57 V DC
GENERAL TECHNICAL DATA	
Operating temperature	-20°C to +55°C
Protection class	IP20
Dimensions	144 x 135 x 34 mm (without antenna connector)