

IoT Wireless Temperature Datalogger for 4 external probes, with built-in 4G modem and Flat Rate SIM Card

code: U0141TGsim



IoT Wireless Datalogger kit with built-in GSM modem and Flat Rate SIM Card allows the instant connection to the COMET Cloud. GSM Datalogger is designed to record temperature from four external Pt1000 probes connected to the terminal board. In case of exceeded set limits e-mail is sent, SMS and JSON messages can be sent via 4G data connection.

Alarms are also indicated locally by LED, LCD and acoustically by built-in beeper.

The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via included USB-C cable.

GSM recorder **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard**.

Technical data

| | |
|---|--|
| TEMPERATURE SENSOR - external probe Pt1000 | |
| Measuring range | -200 to +260 °C |
| Accuracy | ±0.2°C; ±0,2 % of the measurement value in a range of +100 to +260 °C |
| Resolution | 0.1 °C |
| Response time t90 of temperature measurement (temperature step 20°C, air flow approximately 1m/s) | according to the connected probe |
| GSM MODEM PARAMETERS | |
| LTE Cat 1 | LTE FDD/GSM/GPRS/EDGE |
| Supported network types | GSM/GPRS/EDGE 900/1800 MHz LTE FDD B1/B3/B5/B7/B8/B20 |
| GENERAL TECHNICAL DATA | |
| Operating temperature | -20 to +60 °C |
| Channels | 4x external temperature probe |
| Memory | 500,000 values in noncyclic logging mode; 350,000 values in cyclic record mode |
| Recording interval to the internal memory | adjustable from 1 second to 24 hours |
| Recording interval to the COMET Cloud | from 5 minutes |
| Interval for measuring and evaluating alarms | adjustable 1 s, 10 s, 1 min |
| Recording mode | noncyclic - data logging stops after filling the memory cyclic - after filling memory oldest data is overwritten by new |
| Real time clock | year, leap year, month, day, hour, minute, second |
| Power | rechargeable Li-Ion battery A8200, 3.6V/5200mAh |
| Protection class | IP20 |
| Dimensions | 61 x 93 x 53 mm, with antenna 120 x 93 x 53 mm |
| Weight (including batteries) | approx. 270 g |
| Warranty | 3 years |